CS16



Micro walk-behind scrubber-dryer

The CS16 is a compact, reliable, and user-friendly micro scrubber-dryer that provides effective cleaning in tight spaces. Its easy-to-use controls, low-profile design and ergonomic handle provide easy operation. The CS16 is ideal for hard-to-reach spaces in areas such as hospitals, retail stores and offices.

Worry-free operation and maintenance with optional lithium ion batteries.



ECO mode reduces noise level and increases run-time.



Compact storage with handle that folds easily.



Easy-to-remove recovery tank for cleaning and battery access.

Inside the **CS16**

1. **Comfortable grip and adjustable handle** for ergonomic operation
2. **3-Stage vacuum motor** for strong water pick-up
3. **Big capacity:** 15L solution tank 16,5L recovery tank
4. **Parabolic squeegee shape tracks** the movement of the machine for excellent water pick-up
5. **Brush cover** made out of durable material
6. **Simple no-tools,** no-touch brush change system



CS16 specifications

FEATURE	SPECIFICATION		
	AGM Battery	Lithium-Ion Battery	Corded
Cleaning path		350 mm	
Productivity (per hour) Theoretical Max		1.300 m^2	
Estimated coverage		950 m^2	
Max speed		3,5 km/h	
Brush RPM		140	
Brush/pad pressure		25 kg	
Solution tank capacity		15 L	
Recovery tank capacity		16,5 L	
Run time standard | ecomode (up to hours)*	60 minutes | 70 minutes	up to 105 minutes	unlimited
Charging time	7 hours	7 hours (onboard charger) 2 hours (offboard charger)	-
Power voltage	24 V	24 V	240 V
Length x width x height (handle in upright position)		950 x 450 x 1.200 mm	
Length x width x height (storage position with handle folded down)		950 x 450 x 665 mm	
Weight (without Batteries)	36 kg	36 kg	37,5 kg
Sound level (operator's ear)**	68 dBA | 66 dBA (ecomode)	68 dBA | 66 dBA (ecomode)	70 dBa

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.
** Run times are based on Continuous Scrubbing Run Times.*
*** For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.*

For a demonstration or additional information,
call **+32 3 217 94 11** or email **europe@tennantco.com**

cs16-brochure-en-emea 4/25

©2025 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

Tennant Europe
tennant.eu