

T17

T17 heavy-duty battery rider scrubber

An innovative, high-performance battery scrubber focused on delivering customized solutions to meet customer needs. The T17 cleans effectively in just one pass, enhances indoor air quality, and improves operator and supervisor experience, all in one machine!

Available technologies


- ec-H2O™ technology
- Pro-Panel™ LCD Touch Screen or Touch-n-Go™ control module
- IRIS® Asset Manager
- ES® Extended Scrubbing
- High capacity power sources
- Lithium-ion technology


Engineered for **productivity**













1. **Touch-n-Go™ control module with 1-Step™ start button** allows operators quick access to settings without removing hands from the steering wheel. Also available with optional Pro-PanelTM technology.
2. **Car-like propel and brake pedals** allow for easy operation.
3. **Revolutionary patent-pending water trap** helps reduce spills and dripping by providing unrestricted airflow and captures moisture left int he recovery hose on shutdown.
4. **Recovery tank access step** allows easy access to inspect and clean the recovery tank.
5. **Swinging squeegee** provides excellent water recovery to help reduce the risk of slips and falls.
6. **Large battery capacity options,** including lithium-ion to extend runtime. Lithium-ion provides machine availability to customers to confidently transition from engine-powered to battery-powered machines allowing up to 12 hours of run time within a 24 hour period.

Optional accessories



Pressure washer delivers a powerful spray to clean tough soils.



FOPS certified overhead guard protects operators from falling objects.




Rear squeegee protection kit helps prevent squeegee damage.



Live vacuum wand for quickly picking up miscellaneous debris like shrink wrap.

Inside the **T17**




1. **Forward operating position** improves operator safety and visibility.
2. **Full front shroud** ensures operator leg and foot protection.
3. **Wraparound steel bumper** helps protect your investment.
4. **Yellow touch points** save time and ensure proper maintenance.
5. **Dual vacuum fans** with corrosion-resistant impeller designed for long life.
6. **Debris basket** keeps material out of the recovery tank and prevents clogging.
7. **Solution tank surroundings** are engineered to provide maximum visibility, expanding sightlines to the optional dual sweeping side brushes.
8. **Optional fuel cell ready** battery compartment allows use of existing hydrogen fuel cell infrastructure.

Get the performance you need

The T17 scrubbers delivers consistent cleaning results in even the toughest environments with effective scrubbing.



Scrubbing side brush for increased edge reach and 20% wider path



Cylindrical scrub head for scrubbing on rough floor surfaces



Dual sweeping side brushes ensure entire scrub path is swept

T17 specifications

CLEANING SYSTEM	
Scrubbing Path (main scrub deck) | With scrubbing side brush	40 in / 1,015 mm | 52 in / 1,320 mm
Cylindrical brush speed	500 rpm
Cylindrical brush down force (up to)	550 lb / 250 kg
Debris hopper	0.7 ft3 / 20 L
Disk brush speed	315 rpm
Disk brush down force (up to)	550 lb / 250 kg
Solution tank	75 gal / 285 L
Solution capacity (ES®)	115 gal / 435 L
Recovery tank	91.1 gal / 346 L
Vacuum fan (Dual force)	2 x .8hp / 2 x .6 kW
Vacuum speed	14,500 rpm
Vacuum water lift	65 in / 1,650 mm
PROPELLING SYSTEM	
Propel speed forward (transport variable to) | Propel speed forward (scrubbing variable to)	5.5 mph / 9 km / h | 4.0 mph / 6.5 km / h
Gradeability Working | Gradeability Transport (empty to trailering)	5° / 8.7% | 12° / 21%
POWER SOURCES	
Battery selections	36V, 840 AH Wet | 36V, 930 AH C/6 Wet 36V, 456AH Lithium Ion Battery | 36V, 684AH Lithium Ion Battery Lithium-ion batteries have specific charging requirements. Contact your Tennant Representative for charger compatibility information.
Fuel Cell Prep	Contact your Tennant Representative for more information.
MACHINE SPECIFICATIONS	
Length basic machine	88.4 in / 2,245 mm
Width, body	46 in / 1,168 mm
Height (top of steering wheel)	58.25 in / 1,480 mm
With overhead guard	82.5 in / 2,096 mm
Weight empty (no battery)	1,925 lb / 875 kg
Minimum aisle turn	93.25 in / 2,370 mm
WARRANTY	
See your local representative for warranty information	

Specifications subject to change without notice.

Tennant – Reinvent how the world cleans

With a vision to become a global leader in sustainable cleaning innovation that empowers our customers to create a cleaner, safer and healthier world, Tennant creates solutions that are changing the way the world cleans.

We are where you are
Tennant has the industry's largest direct sales and service organization and a well-supported network of authorized distributors worldwide.

Solutions for your unique needs
Whatever your cleaning needs, Tennant offers a variety of high quality equipment to help you increase your cleaning productivity.

Buying, leasing, renting
We offer flexible options to get you the machines you need, however you need them.

Tennant*True*®
Optimize equipment performance and protect your investment with Tennant*True*® parts and service.

For a demonstration or additional information,
call **+32 3 217 94 11** or email **europe@tennantco.com**

t17-brochure-en-emea 12/25

© 2025 Tennant Company. All rights reserved. All indicated Tennant trademarks and logos are property of Tennant Company and/or its affiliated or subsidiary companies. Third party trademarks and logos are property of their respective owners.

Tennant Europe
tennant.eu